

# Technical specifications

## Furniture Linoleum

|   |                         |                |   |
|---|-------------------------|----------------|---|
|  | Total thickness         | EN-ISO 24346   | 2.0 mm  |
|  | Roll width              | EN-ISO 24341   | 1.83 m  |
|  | Roll length             | EN-ISO 24341   | ≤ 30 m  |
|  | Weight                  | EN-ISO 23997   | 2.1 kg/m <sup>2</sup>   |
|  | Indentation-residual    | EN-ISO 24341-1 | < 0.20 mm   |
|  | Light fastness          | EN-ISO 105-B02 | Method 3: blue scale minimum 6.   |
|  | Gloss level             | ISO 2813       | < 5   |
|  | Flexibility             | EN-ISO 24344   | ø 50 mm   |
|  | Resistance to chemicals | EN-ISO 26987   | Resistant to diluted acids, oils, fats and to the conventional solvents.<br>Not resistant to prolonged exposure to alkalis. |
|  | Heat resistance         |                | 70 ° C  |
|  | Body voltage            | EN 1815        | < 2 kV  |
|  | Life Cycle Assessment   |                | LCA is the foundation for securing the lowest environmental impact.   |

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.  
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.  
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

